

# TENDER TEXT



## SPOT LIGHTS

### Bubble

LP-SL181302



## TENDER TEXT

Supply and install Bubble (LP-SL181302) Spot Light by LIGHT PLUS UK. Housing: Die-cast Aluminum. Diffuser: Tempered Frosted Glass or Clear Tempered Glass. Beam Angle: 15° / 24° / 36° / 45°. Color Available: Black/White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 55C°. UGR: <16. LUMINOUS EFFICACY (LM/W): 80. MACADAM: <3. ACCESSORIES AVAILABLE: Honeycomb Louver. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. IK: 06. Or equal and approved.

## DESCRIPTION

Bubble LED Spotlight is a mini and exquisite lamp with high light transmittance. it's offers a very little size in many design styles, without forgetting about the functionality: all the range is characterized by the use high quality LED technology, so the result is a choice of accent light suitable for false ceiling, kitchen cabinet and not only. The possible applications are a multitude. The mini spotlights are all environmental friendly and very useful in a matter of energy and economical saving. The light result is bright, uniform and comfortable. Housing made by die cast aluminum powder coated with choice of RAL colors reflector with pure die cast aluminum diffuser – tempered glass.

## TECHNICAL CHARACTERISTICS

|                 |                                                |
|-----------------|------------------------------------------------|
| Housing         | Die-cast Aluminum                              |
| Diffuser        | Tempered Frosted Glass or Clear Tempered Glass |
| Beam Angle      | 15° / 24° / 36° / 45°                          |
| Color Available | Black/White                                    |
| Lifespan        | >50,000 Hours (L90 B10)                        |
| Reflector       | Aluminium Reflector                            |

|                          |                                          |
|--------------------------|------------------------------------------|
| Voltage                  | AC220~240V                               |
| Working Temperature      | -10C° ~ 55C°                             |
| UGR                      | <16                                      |
| LUMINOUS EFFICACY (LM/W) | 80                                       |
| MACADAM                  | <3                                       |
| ACCESSORIES AVAILABLE    | Honeycomb Louver                         |
| LED Driver               | Light Plus, TriDonic, PHILIPS, OSRAM, MW |
| IP Rating                | 44                                       |
| IK                       | 06                                       |
|                          |                                          |

#### ITEM CODES

| Item Code   | Power | Lamp | Lumen | Dimensions             |
|-------------|-------|------|-------|------------------------|
| LP-SL181302 | 02W   | LED  | 160lm | A41.5 X B30 X C35 mm   |
| LP-SL181303 | 03W   | LED  | 240lm | A41.5 X B30 X C35 mm   |
| LP-SL181305 | 05W   | LED  | 400lm | A49.6 X B28.4 X C42 mm |

#### ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · [info@lightplus.uk](mailto:info@lightplus.uk)

Specifications subject to change without prior notice. Generated 2026-09-23, 15:13.