

TENDER TEXT



SPOT LIGHTS

Kab

LP-SL184110



TENDER TEXT

Supply and install Kab (LP-SL184110) Spot Light by LIGHT PLUS UK. Housing: Die-cast Aluminum. Diffuser: PMMA. Beam Angle: 15° / 24° / 36° / 45°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. UGR: <19. MACADAM: <3. LUMINOUS EFFICACY (LM/W): 120. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. IK: 06. Or equal and approved.

DESCRIPTION

Kab LED Spot Light is a mini and exquisite lamp with high light transmittance PMMA lens. it's offers a very little size in many design styles, without forgetting about the functionality: all the range is characterized by the use high quality LED technology, so the result is a choice of accent light suitable for false ceiling, kitchen cabinet and not only. The possible applications are a multitude. The mini spotlights are all environmental friendly and very useful in a matter of energy and economical saving. The light result is bright, uniform and comfortable. Housing made by die cast aluminium powder coated with choice of RAL colors reflector with pure die cast aluminium diffuser – tempered glass.

TECHNICAL CHARACTERISTICS

Housing	Die-cast Aluminum
Diffuser	PMMA
Beam Angle	15° / 24° / 36° / 45°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector

Voltage	AC220~240V
Working Temperature	-10C° ~ 50C°
UGR	<19
MACADAM	<3
LUMINOUS EFFICACY (LM/W)	120
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	44
IK	06

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL184110	10W	LED	1200lm	A85 X B70 X C75 mm
LP-SL184112	12W	LED	1440lm	A85 X B70 X C75 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.