

TENDER TEXT



SPOT LIGHTS

Giva

LP-SL184407



TENDER TEXT

Supply and install Giva (LP-SL184407) Spot Light by LIGHT PLUS UK. Housing: Die-casting Aluminum. Diffuser: PMMA. Beam Angle: 15° / 24° / 36° / 45°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Deep Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. UGR: <15. LUMINOUS EFFICACY (LM/W): 120. MACADAM: <3. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 08. Or equal and approved.

DESCRIPTION

Giva LED Spot Light is a mini and exquisite lamp with high light transmittance. it offers a very little size in many design styles, without forgetting about the functionality: all the range is characterized by the use high quality LED technology, so the result is a choice of accent light suitable for false ceiling, kitchen cabinet and not only. The possible applications are a multitude. This spotlights are all environmental friendly and very useful in a matter of energy and economical saving. The light result is bright, uniform and comfortable. Housing made by die cast aluminum powder coated with choice of RAL colors reflector.

TECHNICAL CHARACTERISTICS

Housing	Die-casting Aluminum
Diffuser	PMMA
Beam Angle	15° / 24° / 36° / 45°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Deep Reflector

Voltage	AC220~240V
Working Temperature	-10C° ~ 50C°
UGR	<15
LUMINOUS EFFICACY (LM/W)	120
MACADAM	<3
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL184407	07W	LED	840lm	A65 X B86 X C55 mm
LP-SL184410	10W	LED	1200lm	A85 X B105 X C75 mm
LP-SL184412	12W	LED	1440lm	A85 X B105 X C75 mm
LP-SL184420	20W	LED	2400lm	A105 X B125 X C95 mm
LP-SL184430	30W	LED	3600lm	A135 X B125 X C125 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.