

TENDER TEXT



DOWN LIGHTS

Spoter

LP-SL 189235



TENDER TEXT

Supply and install Spoter (LP-SL 189235) Down Light by LIGHT PLUS UK. Housing: Die-casting Aluminum. with White Powder Spraying On The Surface. Diffuser: Glass Diffuser. Beam Angle: 15° / 24° / 36° / 45°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. Or equal and approved.

DESCRIPTION

Spoter LED Spot Light has a strong light without glare, it is a perfect choice for functional observer for high-end residential or hospitality settings. This versatile, elegant architectural spot light will bring pure form, definition and quality light to any space without stealing all the attention. Attractive exclusive spot light for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. Well integrated LED chip and associated dimmable driver. Made of die-cast powder-coated aluminium.

TECHNICAL CHARACTERISTICS

Housing	Die-casting Aluminum. with White Powder Spraying On The Surface
Diffuser	Glass Diffuser
Beam Angle	15° / 24° / 36° / 45°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-10C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL 189235	35W	LED	3150lm	A190XB130XC90mm
LP-SL 189245	45W	LED	4050lm	A190XB130XC90mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.