

TENDER TEXT



SPOT LIGHTS

PRIME

LP-DL918710



TENDER TEXT

Supply and install PRIME (LP-DL918710) Spot Light by LIGHT PLUS UK. Housing: Luminaire Body Of Die-cast Aluminum, White, Powder coated and Heat Sink Form a Compact Unit. Diffuser: Clear Tempered Glass. Beam Angle: 15° / 24° / 38° / 55°. Color Available: White. Reflector: Aluminum Reflector. Lifespan: >50,000 Hours (L80 B10 F10). Voltage: AC220~240V. Working Temperature: -20C° ~ +45C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 40. Or equal and approved.

DESCRIPTION

This focused lighting solution is crafted from robust die-cast aluminum with a protective, high-quality finish, ensuring long term durability and resistance to typical indoor wear. Designed for recessed ceiling installation, it combines a sleek, discreet aesthetic with powerful, energy-efficient LED illumination, enhancing indoor spaces with both elegance and reliable performance.

TECHNICAL CHARACTERISTICS

Housing	Luminaire Body Of Die-cast Aluminum, White, Powder coated and Heat Sink Form a Compact Unit
Diffuser	Clear Tempered Glass
Beam Angle	15° / 24° / 38° / 55°
Color Available	White
Reflector	Aluminum Reflector
Lifespan	>50,000 Hours (L80 B10 F10)
Voltage	AC220~240V
Working Temperature	-20C° ~ +45C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	40

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL918710	10W	LED	900lm	A85 X B49 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.