

TENDER TEXT



DOWN LIGHTS

NOVA

LP-DL918415



TENDER TEXT

Supply and install NOVA (LP-DL918415) Down Light by LIGHT PLUS UK. Housing: Die Cast Aluminum, Highly pure powder coating. Diffuser: Optical PMMA Lens. Beam Angle: 15° / 24° / 36° / 60°. Color Available: White, Black, Silver and Grey. Reflector: Aluminum Reflector. Lifespan: >50,000 Hours (L80 B10). Voltage: AC220~240V. Working Temperature: -30C° ~ +65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. Or equal and approved.

DESCRIPTION

This focused lighting solution is crafted from robust die-cast aluminum with a protective, high-quality finish, ensuring long term durability and resistance to typical indoor wear. Designed for recessed ceiling installation, it combines a sleek, discreet aesthetic with powerful, energy-efficient LED illumination, enhancing indoor spaces with both elegance and reliable performance.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum, Highly pure powder coating.
Diffuser	Optical PMMA Lens
Beam Angle	15° / 24° / 36° / 60°
Color Available	White, Black, Silver and Grey
Reflector	Aluminum Reflector
Lifespan	>50,000 Hours (L80 B10)
Voltage	AC220~240V
Working Temperature	-30C° ~ +65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL918415	15W	LED	1800lm	A105 X B42 mm
LP-DL918420	20W	LED	2400lm	A136 X B50 mm
LP-DL918430	30W	LED	3600lm	A162 X B58 mm
LP-DL918440	40W	LED	4800lm	A213 X B66 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.