

TENDER TEXT



DOWN LIGHTS

Meade

LP-DL2050107



TENDER TEXT

Supply and install Meade (LP-DL2050107) Down Light by LIGHT PLUS UK. Housing: Luminaire Body of die-cast Aluminum, White, powder-coated. Luminaire body and Heat Sink form a Compact Unit. Diffuser: Clear Tempered Glass. Beam Angle: 15° / 24° / 36° / 45°. Color Available: White. Lifespan: >50,000 Hours (L90 B10) / >75,000 Hours (L80 B20) / >100,000 Hours (L70 B50). Reflector: Aluminium Reflector. Voltage: AC100~240V. Working Temperature: -40C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. IK: 08. Or equal and approved.

DESCRIPTION

Attractive adjustable multiple downlights for prestigious lighting of offices, banks, hotels, restaurants, corridors, foyers, sales, exhibition and conference rooms, as well as residential areas. It is well integrated LED chip and dimmable Phase cut-off or DALI driver.

TECHNICAL CHARACTERISTICS

Housing	Luminaire Body of die-cast Aluminum, White, powder-coated. Luminaire body and Heat Sink form a Compact Unit
Diffuser	Clear Tempered Glass
Beam Angle	15° / 24° / 36° / 45°
Color Available	White
Lifespan	>50,000 Hours (L90 B10) / >75,000 Hours (L80 B20) / >100,000 Hours (L70 B50)
Reflector	Aluminium Reflector
Voltage	AC100~240V
Working Temperature	-40C° ~ 50C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL2050107	1X07W	LED	840lm	A115 X B115 X C100 mm
LP-DL2050110	1X10W	LED	1200lm	A115 X B115 X C100 mm
LP-DL2050115	1X15W	LED	1800lm	A115 X B115 X C100 mm
LP-DL2050210	2X10W	LED	2400lm	A230 X B115 X C100 mm
LP-DL2050215	2X15W	LED	3600lm	A230 X B115 X C100 mm
LP-DL2045310	3X10W	LED	3600lm	A285 X B115 X C100 mm
LP-DL2045315	3X15W	LED	5400lm	A285 X B115 X C100 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.