

TENDER TEXT



DOWN LIGHTS

Serie

LP-DL181712



TENDER TEXT

Supply and install Serie (LP-DL181712) Down Light by LIGHT PLUS UK. Housing: Die-casting Aluminum. Diffuser: Tempered Glass Diffuser. Beam Angle: 24° / 38° / 45° / 60°. Color Available: White RAL 9010. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -25°C ~ 50°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. Or equal and approved.

DESCRIPTION

Serie LED Down Light is recessed downlight with die-cast aluminium body, die-cast aluminium heat sink, solid springs and chrome reflector. COB high power LED chip provides perfect combination of high lighting efficiency, comfortable lighting and humanization design, made by high quality Aluminum profile. The item is very professional and it has all the characteristics to be involved in any kind of architectural or design project, it is designed for general lighting applications in office, supermarket, shop, school, hotel, etc.. it is also widely used for public areas, such as stairway, lobby, reception.

TECHNICAL CHARACTERISTICS

Housing	Die-casting Aluminum
Diffuser	Tempered Glass Diffuser
Beam Angle	24° / 38° / 45° / 60°
Color Available	White RAL 9010
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-25°C ~ 50°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL181712	12W	LED	1440lm	A84 x B52 x C75 mm
LP-DL181718	18W	LED	2160lm	A100 x B64 x C90 mm
LP-DL181724	24W	LED	2880lm	A126 x B70 x C115 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.