

TENDER TEXT



DOWN LIGHTS

Spoty IV

LP-DL2038336



TENDER TEXT

Supply and install Spoty IV (LP-DL2038336) Down Light by LIGHT PLUS UK. Housing: Luminaire Body of die-cast Aluminum, White, powder-coated. Luminaire body and Heat Sink form a Compact Unit. Diffuser: Clear Tempered Glass. Beam Angle: 15° / 24° / 36° / 45°. Color Available: White. Lifespan: >50,000 Hours (L80 B10). Reflector: Aluminium Reflector. Voltage: AC 100~240V. Working Temperature: -35C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. Or equal and approved.

DESCRIPTION

Spoty IV attractive downlight for prestigious of offices, banks, hotels, restaurants, corridors, foyers, sales exhibition and conference rooms as well as residential areas. It is well integrated LED Chip and dimmable phase cut-off or DALI Driver.

TECHNICAL CHARACTERISTICS

Housing	Luminaire Body of die-cast Aluminum, White, powder-coated. Luminaire body and Heat Sink form a Compact Unit
Diffuser	Clear Tempered Glass
Beam Angle	15° / 24° / 36° / 45°
Color Available	White
Lifespan	>50,000 Hours (L80 B10)
Reflector	Aluminium Reflector
Voltage	AC 100~240V
Working Temperature	-35C° ~ 65C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	44

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL2038336	3 X 6W	LED	1980lm	A300 X B125 X C55mm
LP-DL2038326	2 X 6W	LED	1320lm	A220 X B125 X C55mm
LP-DL2038316	1 X 6W	LED	660lm	A125 X B125 X C55mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:35.