

TENDER TEXT



DOWN LIGHTS

Spoty III

LP-DL2037320



TENDER TEXT

Supply and install Spoty III (LP-DL2037320) Down Light by LIGHT PLUS UK. Housing: Luminaire Body of die-cast Aluminum White, powder-coated. Luminaire body and Heat Sink form a Compact Unit. Diffuser: Clear Tempered Glass. Beam Angle: 15° / 24° / 36° / 45°. Color Available: White. Lifespan: >50,000 Hours (L80 B10). Reflector: Aluminium Reflector. Voltage: AC100~240V. Working Temperature: -35C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. Or equal and approved.

DESCRIPTION

Spoty III attractive downlight for prestigious of offices, banks, hotels, restaurants, corridors, foyers, sales exhibition and conference rooms as well as residential areas. It is well integrated LED Chip and dimmable phase cut-out or DALI Driver.

TECHNICAL CHARACTERISTICS

Housing	Luminaire Body of die-cast Aluminum White, powder-coated. Luminaire body and Heat Sink form a Compact Unit
Diffuser	Clear Tempered Glass
Beam Angle	15° / 24° / 36° / 45°
Color Available	White
Lifespan	>50,000 Hours (L80 B10)
Reflector	Aluminium Reflector
Voltage	AC100~240V
Working Temperature	-35C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL2037320	3x20W	LED	7200lm	A400 X B140 X C55
LP-DL2037220	2x20W	LED	4800lm	A280 X B140 X C55
LP-DL2037120	1x20W	LED	2400lm	A140 X B140 X C55

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:35.