

TENDER TEXT



DOWN LIGHTS

Panelo III

L+DL-2022-7



TENDER TEXT

Supply and install Panelo III (L+DL-2022-7) Down Light by LIGHT PLUS UK. Panel Light LED: 2835, 26~28lm (High Lumin Chip) CRI>70. Body Material: Aluminium. Beam Angle: 100°. IP Rating: IP40/44. Input: AC 180~265V mark. Voltage: AC220~240V. Working Temperature: -35C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. Or equal and approved.

DESCRIPTION

Panelo III is attractive LED Panel downlight for prestigious lighting of offices, banks, hotels, restaurants, corridors, foyers, sales, exhibition and conference rooms, as well as residential areas.

TECHNICAL CHARACTERISTICS

Panel Light LED	2835, 26~28lm (High Lumin Chip) CRI>70
Body Material	Aluminium
Beam Angle	100°
IP Rating	IP40/44
Input	AC 180~265V mark
Voltage	AC220~240V
Working Temperature	-35C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
-----------	-------	------	-------	------------

L+DL-2022-7	07W	LED	450lm	100 x 100 x 30 mm
L+DL-2022-12	12W	LED	900lm	120 x 120 x 30 mm
L+DL-2022-15	15W	LED	1200lm	145 x 145 x 30 mm
L+DL-2022-18	18W	LED	1530lm	170 x 170 x 40 mm
L+DL-2022-30	30W	LED	2550lm	225 x 225 x 40 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.