

TENDER TEXT



DOWN LIGHTS

Panelo-II

L+DL-2022-7



TENDER TEXT

Supply and install Panelo-II (L+DL-2022-7) Down Light by LIGHT PLUS UK. Panel Light LED: 2835, 26~28lm (High Lumin Chip) CRI>70. Body Material: Aluminium. LGP: PS. Beam Angle: 100°. IP Rating: IP40/44. Input: AC 180~265V mark. Voltage: AC220~240V. Working Temperature: -35C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. Or equal and approved.

DESCRIPTION

Panelo II is attractive LED Panel downlight for prestigious lighting of offices, banks, hotels, restaurants, corridors, foyers, sales, exhibition and conference rooms, as well as residential areas.

TECHNICAL CHARACTERISTICS

Panel Light LED	2835, 26~28lm (High Lumin Chip) CRI>70
Body Material	Aluminium
LGP	PS
Beam Angle	100°
IP Rating	IP40/44
Input	AC 180~265V mark
Voltage	AC220~240V
Working Temperature	-35C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
L+DL-2022-7	07W	LED	700lm	100mm X 30mm
L+DL-2022-12	12W	LED	1200lm	120mm X 30mm
L+DL-2022-15	15W	LED	1500lm	145mm X 30mm
L+DL-2022-18	18W	LED	1800lm	170mm X 40mm
L+DL-2022-30	30W	LED	3000lm	225mm X 40mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.