

TENDER TEXT



DOWN LIGHTS

Down

LP-DL172007



TENDER TEXT

Supply and install Down (LP-DL172007) Down Light by LIGHT PLUS UK. Housing: Die-cast Aluminum Body, White Powder Coated. Diffuser: Tempered Clear Glass. Beam Angle: 120°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. IK: 08. Or equal and approved.

DESCRIPTION

Down LED Down Light Attractive exclusive downlight for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. The light efficiency reach up to 120lm/w with perfect accent lighting performance. That makes it become the priority selected product for commercial lighting. Great cooling fins heat sink design increases the interface between heat sink and air, which makes the heat dissipating performance outstanding and extend the service life of the downlight. Suitable for commercial and residential applications like oce, supermarket, shop, school, hotel, restaurant, workshop, etc.

TECHNICAL CHARACTERISTICS

Housing	Die-cast Aluminum Body, White Powder Coated
Diffuser	Tempered Clear Glass
Beam Angle	120°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-10C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL172007	07W	LED	840lm	A92 x B50 x C75mm
LP-DL172012	12W	LED	1440lm	A135 x B56 x C110mm
LP-DL172015	15W	LED	1800lm	A165 x B63 x C145mm
LP-DL172020	20W	LED	2400lm	A190 x B65 x C170mm
LP-DL172030	30W	LED	3600lm	A230 x B70 x C220mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:31.