

# TENDER TEXT



## DOWN LIGHTS

### Shine

LP-DL181618



## TENDER TEXT

Supply and install Shine (LP-DL181618) Down Light by LIGHT PLUS UK. Housing: Luminaire Body of Die-cast Aluminum and Heat Sink form a Compact Unit, White, Powder-coated. Diffuser: Clear Tempered Glass. Beam Angle: 24° / 38° / 45° / 60°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -25C° ~ 40C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. IK: 08. Or equal and approved.

## DESCRIPTION

Shine LED Down Light is die-cast aluminium body, die-cast aluminium heat sink, solid springs and chrome reflector. COB high power LED chip provides perfect combination of high lighting efficiency, comfortable lighting and humanization design, made by high quality Aluminum profile. The item is very professional and it has all the characteristics to be involved in any kind of architectural or design project.

## TECHNICAL CHARACTERISTICS

|                     |                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------|
| Housing             | Luminaire Body of Die-cast Aluminum and Heat Sink form a Compact Unit, White, Powder-coated |
| Diffuser            | Clear Tempered Glass                                                                        |
| Beam Angle          | 24° / 38° / 45° / 60°                                                                       |
| Color Available     | White                                                                                       |
| Lifespan            | >50,000 Hours (L90 B10)                                                                     |
| Reflector           | Aluminium Reflector                                                                         |
| Voltage             | AC220~240V                                                                                  |
| Working Temperature | -25C° ~ 40C°                                                                                |

|            |                                          |
|------------|------------------------------------------|
| LED Driver | Light Plus, TriDonic, PHILIPS, OSRAM, MW |
| IP Rating  | 54                                       |
| IK         | 08                                       |

#### ITEM CODES

| Item Code   | Power | Lamp | Lumen  | Dimensions            |
|-------------|-------|------|--------|-----------------------|
| LP-DL181618 | 18W   | LED  | 2160lm | A101 x B60 x C85 mm   |
| LP-DL181630 | 30W   | LED  | 3600lm | A140 x B73 x C120 mm  |
| LP-DL181640 | 40W   | LED  | 4800lm | A180 x B94 x C160 mm  |
| LP-DL181650 | 50W   | LED  | 6000lm | A212 x B110 x C195 mm |

#### ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · [info@lightplus.uk](mailto:info@lightplus.uk)

Specifications subject to change without prior notice. Generated 2026-09-23, 15:13.