

TENDER TEXT



DOWN LIGHTS

Polka

LP-DL179015



TENDER TEXT

Supply and install Polka (LP-DL179015) Down Light by LIGHT PLUS UK. Housing: Hard Die-cast Aluminum Body, White Powder Coated. Diffuser: Tempered Frosted Glass Diffuser. Beam Angle: 24° / 38° / 45° / 60°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. Or equal and approved.

DESCRIPTION

Polka LED Down Light is recessed aluminium downlight available in white. This downlight design has been finished with a special paint treatment to ensure an extra-long lifespan and making it suitable for use under eaves and in water areas such as showers. It features semi anti-glare with a deep positioning, and can be installed under insulation using an ICD driver, great thermal management, IP65 waterproof with high protection level, which offers a wider application area.

TECHNICAL CHARACTERISTICS

Housing	Hard Die-cast Aluminum Body, White Powder Coated
Diffuser	Tempered Frosted Glass Diffuser
Beam Angle	24° / 38° / 45° / 60°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL179015	15W	LED	1200lm	A115 X B78 X C95mm
LP-DL179018	18W	LED	1800lm	A135 X B80 X C120mm
LP-DL179030	30W	LED	2400lm	A170 X B95 X C150mm
LP-DL179040	40W	LED	3600lm	A195 X B105 X C170mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.