

TENDER TEXT



DOWN LIGHTS

Lexo

LP-DL179510



TENDER TEXT

Supply and install Lexo (LP-DL179510) Down Light by LIGHT PLUS UK. Housing: Luminaire Body of Die-cast Aluminum, White, Powder-coated. Diffuser: Tempered Frosted or Clear Tempered Glass. Beam Angle: 24° / 38° / 45° / 60°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. Or equal and approved.

DESCRIPTION

Lexo LED Down Light for indoor or outdoor mounting, powerful lumen output via the powerful recessed LED chip. Driver surface-mounted with quick junction box with quick clips for additional looping. Made of die-cast powder-coated aluminium, glass diffuser. Lexo downlight is unique designed with reflector and COB high power LED chip. ADC12 aluminum housing provides excellent thermal dissipation. LED Module design could save SKU and offer an easy module replacement. It supports a great compatibility for non- dim, triac dim, 0-10V, DALI dim with worldwide dimmers.

TECHNICAL CHARACTERISTICS

Housing	Luminaire Body of Die-cast Aluminum, White, Powder-coated
Diffuser	Tempered Frosted or Clear Tempered Glass
Beam Angle	24° / 38° / 45° / 60°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-10C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL179510	10W	LED	1200lm	A110XB53XC90mm
LP-DL179513	13W	LED	1560lm	A110XB53XC90mm
LP-DL179518	18W	LED	2160lm	A145XB65XC120mm
LP-DL179525	25W	LED	3000lm	A190XB75XC160mm
LP-DL179535	35W	LED	4200lm	A190XB75XC160mm
LP-DL179545	45W	LED	5400lm	A225XB87XC200mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.