

TENDER TEXT



TRACK LIGHTS

CAM

LP-TL3010



TENDER TEXT

Supply and install CAM (LP-TL3010) Track Light by LIGHT PLUS UK. Housing: Aluminum. Diffuser: Polycarbonate Lens. Beam Angle: 15° / 24° / 36°. Color Available: White, Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -30C° ~ 65C°. UGR: <22. LUMINOUS EFFICACY (LM/W): 120. MACADAM: <3. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 20 / 44. IK: 06. Or equal and approved.

DESCRIPTION

Cam Led Track Light with Low voltage DC48V magnetic track light is safe without Electric shock. It has an Aluminum adjustable ring changes the viewing angle. The installation of magnetic track system has several types which can meet different design requirements and is easy to install and move. This magnetic track light has the wide beam angle. Application areas: Retail, office, residential, hotels, restaurants, shopping mall, showroom home, shop etc.

TECHNICAL CHARACTERISTICS

Housing	Aluminum
Diffuser	Polycarbonate Lens.
Beam Angle	15° / 24° / 36°
Color Available	White, Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-30C° ~ 65C°
UGR	<22
LUMINOUS EFFICACY (LM/W)	120
MACADAM	<3
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	20 / 44
IK	06

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-TL3010	10W	LED	1200lm	A40 X B100 mm
LP-TL3015	15W	LED	1800lm	A60 X B120 mm
LP-TL2030	30W	LED	3600lm	A68 X B155 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.