

TENDER TEXT



SUSPENDED & PENDANT

Dropy II

LP-PL233510



TENDER TEXT

Supply and install Dropy II (LP-PL233510) Suspended & Pendant by LIGHT PLUS UK. Housing: Die-casting Aluminum. Diffuser: Tempered Glass Diffuser. Beam Angle: 24° / 36° / 45° / 60°. Color Available: White / Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 45C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 20. IK: 08. Or equal and approved.

DESCRIPTION

This pendant light is an anti-glare design. High lumen COB chip and PMMA lens offer a uniform lighting output. AL6063 aluminum lamp body provides excellent heat dissipation. Special lens design reaches anti-glare effect and creates a comfortable visual experience. Multiple beam angle lens optional, modular lens design make a convenient maintenance. Easy installation, recreational for various application.

TECHNICAL CHARACTERISTICS

Housing	Die-casting Aluminum
Diffuser	Tempered Glass Diffuser
Beam Angle	24° / 36° / 45° / 60°
Color Available	White / Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 45C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	20
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-PL233510	10W	LED	1200lm	A65 X B157 X C1265 mm
LP-PL233515	15W	LED	1800lm	A65 X B157 X C1265 mm
LP-PL233520	20W	LED	2400lm	A85 X B178 X C1285 mm
LP-PL233525	25W	LED	3000lm	A85 X B178 X C1285 mm
LP-PL233530	30W	LED	3600lm	A100 X B211 X C1320 mm
LP-PL233540	40W	LED	4800lm	A100 X B211 X C1320 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.