

TENDER TEXT



SUSPENDED & PENDANT

Sparcle

LP-PL247035



TENDER TEXT

Supply and install Sparcle (LP-PL247035) Suspended & Pendant by LIGHT PLUS UK. Housing: Metal Powder Coated Finish. Diffuser: PMMA. Beam Angle: 90° / 120°. Color Available: White, Dark-Gray, Black. Lifespan: >50,000 Hours (L80 B10). Reflector: Aluminium Reflector. Voltage: AC200~240V. Working Temperature: -30C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 20. IK: 06. Or equal and approved.

DESCRIPTION

This pendant offers another option for contemporary indoor lighting solutions. Indoor suspended linear fitting with integrated LED sources and direct light emission structure, with durable white, dark-gray powder coat finish, PMMA diffuser, offering a comfortable discussed light, High transmission opal diffuser, Suspension installation.

TECHNICAL CHARACTERISTICS

Housing	Metal Powder Coated Finish
Diffuser	PMMA
Beam Angle	90° / 120°
Color Available	White, Dark-Gray, Black
Lifespan	>50,000 Hours (L80 B10)
Reflector	Aluminium Reflector
Voltage	AC200~240V
Working Temperature	-30C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	20

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-PL247035	35W	LED	3300lm	A700 X B2045 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:20.