

TENDER TEXT



SUSPENDED & PENDANT

GHALA

LP-PL258020



TENDER TEXT

Supply and install GHALA (LP-PL258020) Suspended & Pendant by LIGHT PLUS UK. Housing: Die cast aluminum. Diffuser: Satinised PMMA cover. Beam Angle: 90° / 120°. Color Available: White/Black. Lifespan: >50,000 Hours (L90 B10 F10). Voltage: 85-265V 50/60Hz. Working Temperature: -30C° ~ +65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. Or equal and approved.

DESCRIPTION

This pendant offers another option for contemporary indoor lighting solutions. Indoor suspended linear fitting with integrated LED sources and direct light emission structure, with durable white, black powder coat finish, PMMA diffuser, offering a comfortable diffused light, High transmission opal diffuser, Suspension installation.

TECHNICAL CHARACTERISTICS

Housing	Die cast aluminum
Diffuser	Satinised PMMA cover
Beam Angle	90° / 120°
Color Available	White/Black
Lifespan	>50,000 Hours (L90 B10 F10)
Voltage	85-265V 50/60Hz
Working Temperature	-30C° ~ +65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	44

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-PL258020	20W	LED	2800lm	A500 X B12mm H
LP-PL258035	35W	LED	4900lm	A500 X B12mm H

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.