

TENDER TEXT



PANEL LIGHTS

Jet

LP-PNL214036



TENDER TEXT

Supply and install Jet (LP-PNL214036) Panel Light by LIGHT PLUS UK. Housing: Body Manufactured in Cold-rolled Steel with Durable White Powder Coat Finish. Diffuser: Double PMMA Opal Diffuser in Arc Shape. Beam Angle: 120°. Color Available: White (other colors available on request). Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -30C°~+60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. IK: 08. Or equal and approved.

DESCRIPTION

The Jet light is direct lighting with louver anti-glare design. Adopt high lumen SMD chip and special lens which provide high light efficiency and uniform light output. It offers the ideal combination of stylish design and optimum performance for both task and general lighting.

TECHNICAL CHARACTERISTICS

Housing	Body Manufactured in Cold-rolled Steel with Durable White Powder Coat Finish
Diffuser	Double PMMA Opal Diffuser in Arc Shape
Beam Angle	120°
Color Available	White (other colors available on request)
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-30C°~+60C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	44
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-PNL214036	36W	LED	3530lm	A596 x B596 x C70 mm
LP-PNL214040	40W	LED	3870lm	A596 x B596 x C70 mm
LP-PNL213532	32W	LED	3390lm	A596 x B596 x C85 mm
LP-PNL213536	36W	LED	3780lm	A596 x B596 x C85 mm
LP-PNL213540	40W	LED	4200lm	A596 x B596 x C85 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.