

TENDER TEXT



PANEL LIGHTS

Hero

LP-PNL216027



TENDER TEXT

Supply and install Hero (LP-PNL216027) Panel Light by LIGHT PLUS UK. Housing: Cold-rolled Steel with Durable White Powder Coat Finish. Diffuser: High Transmission PMMA Opal, Offering a Comfortable Diffused Light. Beam Angle: 90° / 120°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. Or equal and approved.

DESCRIPTION

Hero LED panel light is an elegant high-class indoor lighting. The outer frames are made of aluminum alloy by anodic oxidation. The lighting source is LED. The lighting design and simple appearance, deluxe and high-class , with good lighting eect. LED panel lamp design is unique, the light passes through the high transmittance of light guide plate after the formation of a uniform plane light eect, good uniformity of illuminance, light and soft, comfortable and also bright, can effectively relieve eye fatigue.

TECHNICAL CHARACTERISTICS

Housing	Cold-rolled Steel with Durable White Powder Coat Finish
Diffuser	High Transmission PMMA Opal, Offering a Comfortable Diffused Light
Beam Angle	90° / 120°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-PNL216027	27W	LED	3429lm	A595 x B595 x C95mm
LP-PNL216036	36W	LED	4572lm	A595 x B595 x C95mm
LP-PNL216040	40W	LED	5080lm	A595 x B595 x C95mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.