

TENDER TEXT



PANEL LIGHTS

Brighty

LP-PNL212030



TENDER TEXT

Supply and install Brighty (LP-PNL212030) Panel Light by LIGHT PLUS UK. Housing: Body Manufactured in Cold-rolled Steel with Durable White Powder Coat Finish. Diffuser: Aluminum Louver Reflector with PC Opal. Beam Angle: 120°. Color Available: White (other colors available on request). Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -30C°-+65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. Or equal and approved.

DESCRIPTION

The Brighty light is direct lighting with louver anti-glare design. Adopt high lumen SMD chip and special lens which provide high light efficiency and uniform light output. It offers the ideal combination of stylish design and optimum performance for both task and general lighting.

TECHNICAL CHARACTERISTICS

Housing	Body Manufactured in Cold-rolled Steel with Durable White Powder Coat Finish
Diffuser	Aluminum Louver Reflector with PC Opal
Beam Angle	120°
Color Available	White (other colors available on request)
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-30C°-+65C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	44

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-PNL212030	30W	LED	3600lm	A595 x B595 x C60mm
LP-PNL212038	36W	LED	4560lm	A595 x B595 x C60mm
LP-PNL212040	40W	LED	4800lm	A595 x B595 x C60mm
LP-PNL212048	48W	LED	5760lm	A595 x B595 x C60mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.