

TENDER TEXT



PANEL LIGHTS

Jet II

LP-PNL214536



TENDER TEXT

Supply and install Jet II (LP-PNL214536) Panel Light by LIGHT PLUS UK. Housing: Body Manufactured in Cold-rolled Steel with Durable White Powder Coat Finish. Diffuser: High Transmission PMMA Opal in Arc Shape. Beam Angle: 120°. Color Available: White (other colors available on request). Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -30C°-+60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. IK: 08. Or equal and approved.

DESCRIPTION

The Jet-II light is direct lighting with louver anti-glare design. Adopt high lumen SMD chip and special lens which provide high light efficiency and uniform light output. It offers the ideal combination of stylish design and optimum performance for both task and general lighting.

TECHNICAL CHARACTERISTICS

Housing	Body Manufactured in Cold-rolled Steel with Durable White Powder Coat Finish
Diffuser	High Transmission PMMA Opal in Arc Shape
Beam Angle	120°
Color Available	White (other colors available on request)
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-30C°-+60C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	44
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-PNL214536	36W	LED	3650lm	A1196 x B296 x C70mm
LP-PNL214540	40W	LED	4050lm	A1196 x B296 x C70mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.