

TENDER TEXT



PANEL LIGHTS

Flat II

LP-PNL215020



TENDER TEXT

Supply and install Flat II (LP-PNL215020) Panel Light by LIGHT PLUS UK. Housing: Sheet Steel of Aluminum. Diffuser: PMMA Polycarbonate Lens. Beam Angle: 120°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. Or equal and approved.

DESCRIPTION

Flat-II LED panel light is an elegant high-class indoor lighting. The outer frames are Power CCT Size Lumen made of aluminum alloy by anodic oxidation. Lighting source is LED. The lighting design and simple appearance, deluxe and high-class, with good lighting effect. LED panel lamp design is unique, the light passes through the high transmittance of light guide plate after the formation of a uniform plane light effect, good uniformity of illuminance, light and soft, comfortable and also bright, can effectively relieve eye fatigue.

TECHNICAL CHARACTERISTICS

Housing	Sheet Steel of Aluminum
Diffuser	PMMA Polycarbonate Lens
Beam Angle	120°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-20C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-PNL215020	20W	LED	2400lm	A600 X B300 mm
LP-PNL215025	25W	LED	3000lm	A600 X B300 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.