

TENDER TEXT



PANEL LIGHTS

Hero II

LP-PNL215050



TENDER TEXT

Supply and install Hero II (LP-PNL215050) Panel Light by LIGHT PLUS UK. Housing: 0.6mm Cold-roll Steel under White Powder Coating. Diffuser: High Optical Grade PMMA Opal Diffuser. Beam Angle: 120°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -30C°-+60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. IK: 08. Or equal and approved.

DESCRIPTION

The Hero-II light is indirect lighting with louver anti-glare design. Adopt high lumen and special lens which provide high light efficiency and uniform light output. It offers the ideal combination of stylish design and optimum performance for both task and general lighting.

TECHNICAL CHARACTERISTICS

Housing	0.6mm Cold-roll Steel under White Powder Coating
Diffuser	High Optical Grade PMMA Opal Diffuser
Beam Angle	120°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-30C°-+60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	54
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-PNL215050	50W	LED	5000lm	A1195 x B595 x C85mm
LP-PNL215055	55W	LED	5500lm	A1195 x B595 x C85mm
LP-PNL215060	60W	LED	6000lm	A1195 x B595 x C85mm
LP-PNL215070	70W	LED	7000lm	A1195 x B595 x C85mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.