


TENDER TEXT



PANEL LIGHTS

Flatty

LP-PNL211230



TENDER TEXT

Supply and install Flatty (LP-PNL211230) Panel Light by LIGHT PLUS UK. Housing: Luminaire body of die-cast aluminum, white, powder-coated. Diffuser: PC Diffuser. Beam Angle: 120°. Light Temperature: 3000K, 4000K, 6000K. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. LED Chip: CREE, OSRAM, PHILIPS, TRIDONIC, NICHIA, BRIDGELUX. Control Gear Type: TCI, TRIDONIC, OSRAM, VS, SYLVANIA (Optional Dali Driver). IP Rating: 54. Or equal and approved.

DESCRIPTION

Flatty LED backlit panel adopts high lumen SMD LED with up to 80% energy saving compared to standard CFL. Long a lifetime of 50,000 hours. The top branded driver comes with Triac dim, 0-10V dim, and DALI dim, it has a perfect dimming range and shares great compatibility with worldwide famous brand dimmers. 120° wide beam angle.

TECHNICAL CHARACTERISTICS

Housing	Luminaire body of die-cast aluminum, white, powder-coated.
Diffuser	PC Diffuser
Beam Angle	120°
Light Temperature	3000K, 4000K, 6000K
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-10C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
LED Chip	CREE, OSRAM, PHILIPS, TRIDONIC, NICHIA, BRIDGELUX.
Control Gear Type	TCI, TRIDONIC, OSRAM, VS, SYLVANIA (Optional Dali Driver)
IP Rating	54

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-PNL211230	30W	LED	3600lm	A595 X B595 X C30 mm
LP-PNL211236	36W	LED	4320lm	A595 X B595 X C30 mm
LP-PNL211240	40W	LED	4800lm	A595 X B595 X C30 mm
LP-PNL211245	45W	LED	5400lm	A595 X B595 X C30 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.