

TENDER TEXT



PANEL LIGHTS

Prism

L +PNL7035-30



TENDER TEXT

Supply and install Prism (L +PNL7035-30) Panel Light by LIGHT PLUS UK. Housing: Made of thermos painted aluminium coated. Diffuser: Micro-Prismatic. Beam Angle: 120°. Color Available: White. Lifespan: >50,000 Hours (L80 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20Co ~ +50Co. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. IK: 08. Or equal and approved.

DESCRIPTION

Prism LED panel adopts high lumen SMD LED with up to 80% energy saving compared to standard CFL. Long a lifetime of 50,000 hours. The top branded driver comes with Triac dim, 0-1 OV dim, and DALI dim, it has a perfect dimming range and shares great compatibility with worldwide famous brand dimmers. 120° wide beam angle. The ultra-slim profile fits seamlessly into any workplace. It is available in various installation ways: embedded into the ceiling, suspended with hanging wires, surface mounted in a concrete ceiling by using a surface mounting frame.

TECHNICAL CHARACTERISTICS

Housing	Made of thermos painted aluminium coated.
Diffuser	Micro-Prismatic
Beam Angle	120°
Color Available	White
Lifespan	>50,000 Hours (L80 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-20Co ~ +50Co
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
L +PNL7035-30	30W	LED	3600lm	A595 x B595 x C7.5mm
L+PNL7035-36	36W	LED	4320lm	A595 x B595 x C7.5mm
L+PNL7035-40	40W	LED	4800lm	A595 x B595 x C7.5mm
L+PNL7035-45	45W	LED	5400lm	A595 x B595 x C7.5mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.