

TENDER TEXT



PANEL LIGHTS

Luxy II

LP-7032-SMT-36



TENDER TEXT

Supply and install Luxy II (LP-7032-SMT-36) Panel Light by LIGHT PLUS UK. Housing: Sheet Steel of Aluminum. Diffuser: PMMA Polycarbonate Lens. Beam Angle: 120°. Color Available: White. Lifespan: >50,000 Hours (L80 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44 / 54. Or equal and approved.

DESCRIPTION

Luxy LED panel adopts high lumen SMD LED with up to 80% energy saving compared to standard CFL. Long a lifetime of 50,000 hours. The top branded driver comes with Triac dim, 0-10V dim, and DALI dim, it has a perfect dimming range and shares great compatibility with worldwide famous brand dimmers. 120° wide beam angle. The ultra-slim profile fits seamlessly into any workplace. It is available in various installation ways: embedded into the ceiling, suspended with hanging wires, surface mounted in a concrete ceiling by using a surface mounting frame.

TECHNICAL CHARACTERISTICS

Housing	Sheet Steel of Aluminum
Diffuser	PMMA Polycarbonate Lens
Beam Angle	120°
Color Available	White
Lifespan	>50,000 Hours (L80 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-20C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	44 / 54

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-7032-SMT-36	36W	LED	4320lm	A595 x B595 x C29mm
LP-7032-SMT-40	40W	LED	4800lm	A595 x B595 x C29mm
LP-7032-SMT-45	45W	LED	5400lm	A595 x B595 x C29mm
LP-7032-SMT-50	50W	LED	6000lm	A595 x B595 x C29mm
LP-7032-SMT-60	60W	LED	7200lm	A595 x B595 x C29mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:35.