

TENDER TEXT



PANEL LIGHTS

Del Panelo

LP-IL2940100



TENDER TEXT

Supply and install Del Panelo (LP-IL2940100) Panel Light by LIGHT PLUS UK. Housing: Die-Cast Aluminum. Diffuser: PMMA Polycarbonate. Beam Angle: 120°. Color Available: White. Lifespan: >50,000 Hours (L80 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C°-+50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. UGR: <19. SDCM: 2.0. IP Rating: 54. IK: 02. Or equal and approved.

DESCRIPTION

Del Panelo LED panel adopts high lumen SMD LED with up to 80% energy saving compared to standard CFL. Long a lifetime of 50,000 hours. The top branded driver comes with Triac dim, O-IOV dim, and DALI dim, it has a perfect dimming range and shares great compatibility with worldwide famous brand dimmers. 120° wide beam angle.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum
Diffuser	PMMA Polycarbonate
Beam Angle	120°
Color Available	White
Lifespan	>50,000 Hours (L80 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C°-+50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

UGR	<19
SDCM	2.0
IP Rating	54
IK	02

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-IL2940100	100W	LED	12000lm	A236 x B101 mm
LP-IL2940150	150W	LED	18000lm	A286 x B106 mm
LP-IL2940240	240W	LED	28800lm	A336 x B115 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:36.