

TENDER TEXT



INDUSTRIAL LIGHTS

Parky II

LP-IL82120



TENDER TEXT

Supply and install Parky II (LP-IL82120) Industrial Light by LIGHT PLUS UK. Housing: Made of Polycarbonate raw material and GRP. shatterproof, radiation protection, UV with high mechanical resistance & with stainless steel Clip. Diffuser: PMMA Polycarbonate milky anti glare with anti yellowing unbreackable (specially for LED) diffuser. UV stabilized with longitudinal striations for a better control of glare and a high light output. Beam Angle: 20° / 40°. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 08. Standards: Designed and manufactured to comply with EN 60598. Or equal and approved.

DESCRIPTION

This LED luminaire high efficiency LED system produces high performances of luminous lux with various color temperature illumination.

TECHNICAL CHARACTERISTICS

Housing	Made of Polycarbonate raw material and GRP. shatterproof, radiation protection, UV with high mechanical resistance & with stainless steel Clip.
Diffuser	PMMA Polycarbonate milky anti glare with anti yellowing unbreackable (specially for LED) diffuser. UV stabilized with longitudinal striations for a better control of glare and a high light output.
Beam Angle	20° / 40°
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66
IK	08
Standards	Designed and manufactured to comply with EN 60598

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-IL82120	20W	LED	2200lm	A1200 x B95 x C75 mm
LP-IL82140	40W	LED	4400lm	A1200 x B95 x C75 mm
LP-IL82160	60W	LED	6600lm	A1200 x B95 x C75 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:32.