

TENDER TEXT



INDUSTRIAL LIGHTS

ANDREW III

LP-IL2940100



TENDER TEXT

Supply and install ANDREW III (LP-IL2940100) Industrial Light by LIGHT PLUS UK. Housing: Die-Cast Aluminum. Diffuser: Polycarbonate Optical Lens. Beam Angle: 24° / 36° / 45° / 60° / 90°. Color Available: Black, Gray, White. Lifespan: >50,000 Hours (L80 BIO). Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 08. Or equal and approved.

DESCRIPTION

Andrew III LED High Bay is High quality light source. Combination of multiple high-power LEDs features. As a new type of high bay light, it distributes light by lens instead of additional reflector. which avoids the occurrence of situations like easy deformation that usually resulted from the classic LED high bay light in transportation.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum
Diffuser	Polycarbonate Optical Lens
Beam Angle	24° / 36° / 45° / 60° / 90°
Color Available	Black, Gray, White
Lifespan	>50,000 Hours (L80 BIO)
Voltage	AC220~240V
Working Temperature	-10C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-IL2940100	100W	LED	12000lm	A236 x B101 mm
LP-IL2940150	150W	LED	18000lm	A286 x B106 mm
LP-IL2940240	240W	LED	28800lm	A336 x B115 mm
LP-IL2940300	300W	LED	36000lm	A336 x B115 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:31.