

TENDER TEXT



INDUSTRIAL LIGHTS

Leo

LP-IL294020



TENDER TEXT

Supply and install Leo (LP-IL294020) Industrial Light by LIGHT PLUS UK. Housing: Injection moulded, in grey polycarbonate, vandal resistant, UV stabilized, high mechanical resistance due to the frame reinforced by internal ribbing. Diffuser: Injected molded in polycarbonate with internal ribbing for greater lighting control, in V2 self-extinguishing, UV-stabilized material, Equipped with stainless steel screw clamping. Beam Angle: 120°. Color Available: Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. Or equal and approved.

DESCRIPTION

Leo is designed for fast and easy installation. The product range features a sleek design that emphasises the unique features of the latest LED technology, offering extremely low energy consumption, high impact resistance and simple installation. The LED luminaires can replace high-flux fluorescents and lowbays. Leo, the first luminaire with a compact design, with through wiring and excellent efficiency. The right solution for a fast return on investment. Made of technopolymeric polycarbonate, with stainless steel cables for suspension application. The diffuser is made of optic polycarbonate.

TECHNICAL CHARACTERISTICS

Housing	Injection moulded, in grey polycarbonate, vandal resistant, UV stabilized, high mechanical resistance due to the frame reinforced by internal ribbing
Diffuser	Injected molded in polycarbonate with internal ribbing for greater lighting control, in V2 self-extinguishing, UV-stabilized material, Equipped with stainless steel screw clamping.
Beam Angle	120°

Color Available	Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-IL294020	20W	LED	3000lm	A560 x B72 x C78 mm
LP-IL294030	30W	LED	4500lm	A560 x B72 x C78 mm
LP-IL294040	40W	LED	6000lm	A1170 x B72 x C78mm
LP-IL294060	60W	LED	9000lm	A1170 x B72 x C78mm
LP-IL294060	60W	LED	9000lm	A1470 x B72 x C78mm
LP-IL294075	75W	LED	11250lm	A1470 x B72 x C78mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.