


TENDER TEXT



INDUSTRIAL LIGHTS

Parky

L+IND-502020



TENDER TEXT

Supply and install Parky (L+IND-502020) Industrial Light by LIGHT PLUS UK. Housing: Injection Moulded, in Grey 421C, Vandal Resistant, UV Stabilized, High Mechanical Resistance Due to the Frame Reinforced by Internal Rribbing. Diffuser: Injection Moulded, in V2 self-extinguishing Polycarbonate, UV Stabilized, clear Polycarbonate, Prismatic Inside for Better Light Control & High Lighting Performance. The External Smooth Finish Facilitates Cleaning, Essential to Maintain Maximum Lighting Efficiency. Beam Angle: 120°. Color Available: Grey 421C. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 08. Or equal and approved.

DESCRIPTION

Parky LED lighting fitting made of high quality polycarbonate. The product range of Parky waterproof LED lights, made entirely in polycarbonate. Suitable for industrial environments between 2 and 9 meters in height, The several fixing ways and the strength of materials make parky a durable and reliable solution for application in industrial and commercial areas. Parky is made of technopolymeric polycarbonate, with stainless steel cables for suspension application. The diffuser is made of optic polycarbonate and the closing hangs are included.

TECHNICAL CHARACTERISTICS

Housing	Injection Moulded, in Grey 421C, Vandal Resistant, UV Stabilized, High Mechanical Resistance Due to the Frame Reinforced by Internal Rribbing
Diffuser	Injection Moulded, in V2 self-extinguishing Polycarbonate, UV Stabilized, clear Polycarbonate, Prismatic Inside for Better Light Control & High Lighting Performance. The External Smooth Finish Facilitates Cleaning, Essential to Maintain Maximum Lighting Efficiency.
Beam Angle	120°
Color Available	Grey 421C

Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
L+IND-502020	20W	LED	2000lm	A600 x B70 x C62 mm
L+IND-502030	30W	LED	3000lm	A1200 x B70 x C62 mm
L+IND-502040	40W	LED	4000lm	A1200 x B70 x C62 mm
L+IND-502050	50W	LED	5000lm	A1500 x B70 x C62 mm
L+IND-502060	60W	LED	6000lm	A1500 x B70 x C62 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:32.