

TENDER TEXT



INDUSTRIAL LIGHTS

Fact

LP-IL295020



TENDER TEXT

Supply and install Fact (LP-IL295020) Industrial Light by LIGHT PLUS UK. Housing: Injection Molded, in RAL 7035 Grey Polycarbonate, Vandal Resistant, UV Stabilized, High Mechanical Resistance Due to the Frame Reinforced by Internal Ribbing. Diffuser: Injection Moulded, in V2 self-extinguishing Polycarbonate, UV Stabilized, Clear Polycarbonate, Prismatic Inside for Better Light Control & High Lighting Performance. The External Smooth Finish Facilitates Cleaning, Essential to Maintain Maximum Lighting Efficiency. Beam Angle: 120°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 08. Or equal and approved.

DESCRIPTION

Fact LED lighting fitting made of high quality polycarbonate. The product range of Fact waterproof LED lights, made entirely in polycarbonate. Suitable for industrial environments between 2 and 9 meters in height, The several fixing ways and the strength of materials make Fact a durable and reliable solution for application in industrial and commercial areas. Fact is made of technopolymeric polycarbonate, with stainless steel cables for suspension application. The diffuser is made of optic polycarbonate and the closing hangs are included.

TECHNICAL CHARACTERISTICS

Housing	Injection Molded, in RAL 7035 Grey Polycarbonate, Vandal Resistant, UV Stabilized, High Mechanical Resistance Due to the Frame Reinforced by Internal Ribbing
Diffuser	Injection Moulded, in V2 self-extinguishing Polycarbonate, UV Stabilized, Clear Polycarbonate, Prismatic Inside for Better Light Control & High Lighting Performance. The External Smooth Finish Facilitates Cleaning, Essential to Maintain Maximum Lighting Efficiency.
Beam Angle	120°

Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-IL295020	20W	LED	3000lm	A650 xB117 x C70 mm
LP-IL295036	36W	LED	5400lm	A1250 xB117 x C70 mm
LP-IL295040	40W	LED	6000lm	A1250 xB117 x C70 mm
LP-IL295050	50W	LED	7500lm	A1250 xB117 x C70 mm
LP-IL295055	55W	LED	8250lm	A1250 xB117 x C70 mm
LP-IL295060	60W	LED	9000lm	A1550 x B117 x C70 mm
LP-IL295070	70W	LED	10500lm	A1550 x B117 x C70 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.