

TENDER TEXT



INDUSTRIAL LIGHTS

Indu

LP-IL291020-2FT



TENDER TEXT

Supply and install Indu (LP-IL291020-2FT) Industrial Light by LIGHT PLUS UK. Housing: Injection Moulded, in Grey Polycarbonate, Vandal Resistant, UV Stabilized, High Mechanical Resistance due to the Frame Reinforced by Internal Ribbing. Diffuser: Injected Molded in Polycarbonate with Internal Ribbing for Greater Lighting Control, in V2 self-extinguishing, UV-stabilized Material, Equipped with Stainless Steel Screw Clamping. Beam Angle: 120°. Color Available: Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 08. Or equal and approved.

DESCRIPTION

Indu is IP66 luminaire for mounting on ceiling. Made of UV-stabilised polycarbonate. Indu LED waterproof is a very hardy luminaire, especially suitable for pig farms and the like. The LED compartment is IP66K protected to withstand ammonia gasses in such environments. The luminaire housing is made of hard UV-stabilised and anti-chemical coated polycarbonate. The coating is resistant to ammonia, washing detergents etc, and makes it suitable also for car wash halls and similar. It is easy to install by just snapping into mounting clips and using the unique one-hand closing mechanism at both ends. The looping options with double cable gland in each end and through wiring gives full flexibility for larger installations.

TECHNICAL CHARACTERISTICS

Housing	Injection Moulded, in Grey Polycarbonate, Vandal Resistant, UV Stabilized, High Mechanical Resistance due to the Frame Reinforced by Internal Ribbing.
Diffuser	Injected Molded in Polycarbonate with Internal Ribbing for Greater Lighting Control, in V2 self-extinguishing, UV-stabilized Material, Equipped with Stainless Steel Screw Clamping.

Beam Angle	120°
Color Available	Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-IL291020-2FT	20W	LED	3000lm	A650 x B97 x C82 mm
LP-IL291020	20W	LED	3000lm	A11220 x B97 x C82 mm
LP-IL291036	36W	LED	5400lm	A1220 x B97 x C82 mm
LP-IL291045	45W	LED	6750lm	A1220 x B97 x C82 mm
LP-IL291036-5FT	36W	LED	5400lm	A1560 x B97 x C82 mm
LP-IL291054-5FT	54W	LED	8100lm	A1560 x B97 x C82 mm
LP-IL291060-5FT	60W	LED	9000lm	A1560 x B97 x C82 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.