

TENDER TEXT



LED STRIP LIGHTS

Flexy

LP-SRLV4.8



TENDER TEXT

Supply and install Flexy (LP-SRLV4.8) LED Strip Light by LIGHT PLUS UK. Housing: Anti-yellowing & Heat Resisting Silicone Glue Extrusion Chemical Resistance Acid. Diffuser: Milky White Silicone. Beam Angle: 120°. Color Available: Milky. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: 24V DC. Working Temperature: -20C° ~ 60C°. Standard Length: 5000 mm. Lead Cable: 300 mm. Bending: Vertical bending only, minimum bending diameter 200 mm. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 68. IK: 08. Or equal and approved.

DESCRIPTION

IP68 flexible dot free linear LED light line with a 16 mm x 16 mm (W x H) cross section. UV resistance, chemical stability against urban gases and protection against abrasion. Vertical bending only, excellent solution for indoor/outdoor organic facade accent lighting or decorative applications requiring IP68 ingress.

TECHNICAL CHARACTERISTICS

Housing	Anti-yellowing & Heat Resisting Silicone Glue Extrusion Chemical Resistance Acid
Diffuser	Milky White Silicone
Beam Angle	120°
Color Available	Milky
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	24V DC

Working Temperature	-20C° ~ 60C°
Standard Length	5000 mm
Lead Cable	300 mm
Bending	Vertical bending only, minimum bending diameter 200 mm
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	68
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SRLV4.8	4.8 W/M	LED	528lm/m	16 X 16 mm
LP-SRLV9.6	9.6 W/M	LED	1056lm/m	16 X 16 mm
LP-SRLV12	12 W/M	LED	1320lm/m	16 X 16 mm
LP-SRLV14	14 W/M	LED	1540lm/m	16 X 16 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.