

TENDER TEXT



LED STRIP LIGHTS

Flexy Neo

LP+STR-12W



TENDER TEXT

Supply and install Flexy Neo (LP+STR-12W) LED Strip Light by LIGHT PLUS UK. Housing: PCB Anti-yellowing & Heat Resisting Silicone Glue. Diffuser: Milky White Silicone. Beam Angle: 120°. Color Available: Milky. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: 220~AC. Working Temperature: -20C° ~ +60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

Ip65 flexible LED light line with a 8 mm cross section. UV resistance, chemical stability against urban gases and protection against abrasion. Vertical bending only, excellent solution for indoor/outdoor organic facade accent lighting or decorative applications requiring IP65 ingress.

TECHNICAL CHARACTERISTICS

Housing	PCB Anti-yellowing & Heat Resisting Silicone Glue
Diffuser	Milky White Silicone
Beam Angle	120°
Color Available	Milky
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	220~AC
Working Temperature	-20C° ~ +60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP+STR-12W	12W/M	LED	140lm/W	10000 X 11 X 19 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:21.