

TENDER TEXT



WALL SURFACE

Cascade

LP-ODL377245



TENDER TEXT

Supply and install Cascade (LP-ODL377245) Wall Surface by LIGHT PLUS UK. Housing: Powder Coated Die cast Aluminum. Diffuser: Tempered Glass Diffuser. Beam Angle: 60°. Color Available: White & Black. Lifespan: >50,000 Hours (L80 B10 F10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ +60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. UGR<: 20. Or equal and approved.

DESCRIPTION

Cascade LED slim wall packs deliver full cutout or semi cutout light distribution. The innovative pivoting head design aims the light precisely. Suitable for applications including pathways, perimeter lighting and building entryways. This LED wall pack fixtures can be mounted on surface/facade, whether you have a new construction or upgrade application.

TECHNICAL CHARACTERISTICS

Housing	Powder Coated Die cast Aluminum
Diffuser	Tempered Glass Diffuser
Beam Angle	60°
Color Available	White & Black
Lifespan	>50,000 Hours (L80 B10 F10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ +60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	10
UGR<	20

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL377245	45W	LED	5400lm	A138 X B240 X C211mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.