

TENDER TEXT



CEILING SURFACE LIGHTS

Pop Square

LP-ODL233845



TENDER TEXT

Supply and install Pop Square (LP-ODL233845) Ceiling Surface Light by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: Tempered Glass Diffuser. Beam Angle: 25° / 40° / 60°. Color Available: White & Black. Lifespan: >50,000 Hours (L80 B10 F10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ +60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. UGR<: 19. Or equal and approved.

DESCRIPTION

Pop square lamp adopts straight forward design with stylish appearance with high quality LED chip with high lumen and pure color. The built-in power supply with high conversion efficiency is stable and reliable. it is very suitable for star hotel, restaurant, shopping mall, villa, residence and other high-end projects.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	Tempered Glass Diffuser
Beam Angle	25° / 40° / 60°
Color Available	White & Black
Lifespan	>50,000 Hours (L80 B10 F10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ +60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	10
UGR<	19

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL233845	45W	LED	5400lm	A86 X B140 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:31.