

TENDER TEXT



CEILING SURFACE LIGHTS

Sunny II

LP-ODL343018



TENDER TEXT

Supply and install Sunny II (LP-ODL343018) Ceiling Surface Light by LIGHT PLUS UK. Housing: Fire Rated -vandal Proof PC. Diffuser: 94-v0 Fire-rated PC Diffuser. Beam Angle: 120°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ +50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Sunny-II LED with easy installation ,this light adopts die-cast aluminum body and 94-v0 fire-rated PC cover ,color changeable function make this bulkhead can change color temperature from warm white to cool white., size 250mm X 59mm ,this bulkhead ideal Applications that require continuous light good to provide high bright lighting to stairway, lobby, reception, corridors etc.

TECHNICAL CHARACTERISTICS

Housing	Fire Rated -vandal Proof PC
Diffuser	94-v0 Fire-rated PC Diffuser
Beam Angle	120°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-10C° ~ +50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL343018	18W	LED	1800lm	A280 X B280 X C49 mm
LP-ODL343025	25W	LED	2500lm	A300 X B300 X C50 mm
LP-ODL343030	36W	LED	3000lm	A300 X B300 X C50 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.