

TENDER TEXT



CEILING SURFACE LIGHTS

Moon II

LP-ODLV18



TENDER TEXT

Supply and install Moon II (LP-ODLV18) Ceiling Surface Light by LIGHT PLUS UK. Housing: High quality PC. Diffuser: Yellowing resistance PC. Beam Angle: 60° / 90°. Color Available: White and Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -30C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. Or equal and approved.

DESCRIPTION

Moon-II LED ceiling light, super slim and minimalistic design; it is a faultless combination and deduction of smooth lines, making itself impregnated with ceiling perfectly. Elegant design with soft and even light output realizes a perfect blend of craft and art. High quality PC lamp body promises a higher production efficiency and more stable product quality without any subsequent process. Superior PC diffuser with excellent performance, fire rated UL94-V0, aging resistance and yellowing resistance make this ceiling light with longer lifespan.

TECHNICAL CHARACTERISTICS

Housing	High quality PC
Diffuser	Yellowing resistance PC
Beam Angle	60° / 90°
Color Available	White and Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-30C° ~ 55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODLV18	18W	LED	2160lm	A58 X B300 mm
LP-ODLV25	25W	LED	3000lm	A66 X B400 mm
LP-ODLV30	30W	LED	3600lm	A66 X B400 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.