

TENDER TEXT



WALL SURFACE

Doomy

LP-553118



TENDER TEXT

Supply and install Doomy (LP-553118) Wall Surface by LIGHT PLUS UK. Housing: Injection moulded thermo polycarbonate (PMMA) material reinforced with fibber glass. Diffuser: Opal injection moulded polycarbonate diffuser. Beam Angle: 15° / 24° / 36° / 45°. Color Available: White, Black and Grey. Reflector: High purity anodized aluminum reflector. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. Standards: Designed and Manufactured to comply with EN 60598. Or equal and approved.

DESCRIPTION

Indoor and outdoor ceiling light fixture suitable for homes, shops, offices production sites.

TECHNICAL CHARACTERISTICS

Housing	Injection moulded thermo polycarbonate (PMMA) material reinforced with fibber glass.
Diffuser	Opal injection moulded polycarbonate diffuser
Beam Angle	15° / 24° / 36° / 45°
Color Available	White, Black and Grey
Reflector	High purity anodized aluminum reflector
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	44
Standards	Designed and Manufactured to comply with EN 60598

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-553118	18W	LED	840lm	A120 X B32 mm
LP-553132	26/36W	LED	1440lm	A170 X B32 mm
LP-554218	2X18W	LED	2400lm	A255 X B32 mm
LP-554226	2X26W	LED	1440lm	A170 X B32 mm

ACCESSORIES

None