

TENDER TEXT



WALL SURFACE

Pointy

LP-ODL375025



TENDER TEXT

Supply and install Pointy (LP-ODL375025) Wall Surface by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: Glass Diffuser. Beam Angle: 15° / 30° / 45° / 60°. Color Available: Black, White & Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC100~277V. Working Temperature: -30C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 08. Or equal and approved.

DESCRIPTION

Pointy LED slim wall packs deliver full cutout or semi cutout light distribution. The innovative pivoting head design aims the light precisely and adjusts up to 20 degrees for forward throw illumination. Suitable for up to 25 foot mounting for applications including pathways, perimeter lighting and building entryways. This LED wall pack fixtures can be mounted on surface/facade, whether you have a new construction or upgrade application.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	Glass Diffuser
Beam Angle	15° / 30° / 45° / 60°
Color Available	Black, White & Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC100~277V
Working Temperature	-30C° ~ 50C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL375025	25W	LED	3000lm	A223xB193xC114 mm
LP-ODL375035	35W	LED	4200lm	A223xB193xC114 mm
LP-ODL375070	70W	LED	8400lm	A334xB281xC281 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.