

TENDER TEXT



WALL SURFACE

Bulky

LP-ODL373028



TENDER TEXT

Supply and install Bulky (LP-ODL373028) Wall Surface by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: Clear and Frosted Diffuser Glass. Beam Angle: 45° / 60° / 90°. Color Available: Black, White & Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Glass Reflector. Voltage: AC220~240V. Working Temperature: -30C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 10. Or equal and approved.

DESCRIPTION

Bulky LED wall pack delivers the perfect illumination for outdoor security lighting, wall perimeter lighting, garages, large backyards, commercial loading bays, warehouses, apartment complexes, hotels and oce and retail complexes. Constructed with both die-casting aluminum with a commercial-grade power coat bronze finish, an impact-resistant tempered glass lens, and maintenance-free LEDs, the commercial wall pack lighting ensure high performance over 50,000-Hours.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	Clear and Frosted Diffuser Glass
Beam Angle	45° / 60° / 90°
Color Available	Black, White & Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Glass Reflector
Voltage	AC220~240V
Working Temperature	-30C° ~ 65C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL373028	28W	LED	3780lm	A241 X B372 X C196 mm
LP-ODL373040	40W	LED	5400lm	A241 X B372 X C196 mm
LP-ODL373050	50W	LED	6750lm	A241 X B372 X C196 mm
LP-ODL373060	60W	LED	6750lm	A193 X B270 X C168 mm
LP-ODL373080	80W	LED	8100lm	A193 X B270 X C168 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.