

TENDER TEXT



WALL SURFACE

Look II

LP-ODL374615



TENDER TEXT

Supply and install Look II (LP-ODL374615) Wall Surface by LIGHT PLUS UK. Housing: Aluminum. Diffuser: Glass Diffuser. Beam Angle: 120°. Color Available: Black, White & Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -30C° ~ 45C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Look-II Wall pack lights, otherwise known as exterior building lights are special kinds of lights designed to be mounted on the outside part of commercial building walls. This Wall packs are designed with high intensity lamp heads that are energy efficient, durable and with low level of light pollution. Among the benefits of this light is its ability to illuminate specific areas outside the building.

TECHNICAL CHARACTERISTICS

Housing	Aluminum
Diffuser	Glass Diffuser
Beam Angle	120°
Color Available	Black, White & Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-30C° ~ 45C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL374615	15W	LED	1350lm	A260 X B130 X C116 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.