

TENDER TEXT



WALL SURFACE

Sidy II

LP-ODL372506



TENDER TEXT

Supply and install Sidy II (LP-ODL372506) Wall Surface by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: 94-v0 Fire-rated PC Diffuser. Beam Angle: 15° / 24° / 36°. Color Available: Black & White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~277V. Working Temperature: -30C° ~ 45C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Sidy-II, the high efficient LED system provides excellent result in luminous flux, light brightness, light uniformity and light pleasantness. Available in -up or up-and down light option. Sidy-II LED wall light looks fabulous at the entrance to any modern home, with its light that can optionally be used either side of a door way for a beautiful framing effect.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	94-v0 Fire-rated PC Diffuser
Beam Angle	15° / 24° / 36°
Color Available	Black & White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~277V
Working Temperature	-30C° ~ 45C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL372506	2X6W	LED	1440lm	A60 X B155 X C118mm
LP-ODL372512	2X12W	LED	2880lm	A108 X B258 X C167mm
LP-ODL372515	2X15W	LED	3600lm	A108 X B258 X C167mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.