

TENDER TEXT



WALL SURFACE

Moony

LP-ODL346012



TENDER TEXT

Supply and install Moony (LP-ODL346012) Wall Surface by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: 94-v0 Fire-rated PC Diffuser. Beam Angle: 60° / 90°. Color Available: Black, White & Dark Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~277V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Visually, Moony External Wall light led impresses with its unique design as well as the tactile appeal. Smiley-face design on the wall makes everyone feel warm and cozy. Automatic water drainage system is equipped on the bottom of the lamp, which makes the lamp IP65 waterproof. The lamp heat sink adopts die-casting aluminum ADC12 with very good heat dissipation, spray powder surface treatment makes the lamp ageing-resistant and corrosion resistant. Lamp cover adopts UL94-V0 fire rated milky PC material with even and soft light output. The build-in terminal block makes installation and maintenance more convenient. The lamp adopts high quality and stable LED with long lifespan, no heat radiation and no harm to eyes and skin. It is a green and environmentally friendly lighting product.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	94-v0 Fire-rated PC Diffuser
Beam Angle	60° / 90°
Color Available	Black, White & Dark Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector

Voltage	AC220~277V
Working Temperature	-10C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL346012	12W	LED	1440lm	A159 X B65.5 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.