

TENDER TEXT



WALL SURFACE

Shade

LP-ODL348012



TENDER TEXT

Supply and install Shade (LP-ODL348012) Wall Surface by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: 94-v0 Fire-rated PC diffuser. Beam Angle: 90°. Color Available: White, Black & Dark-Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~2240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Stylish, cost-effective and reliable, they bring light to interior and exterior architecture worldwide. A great looking outdoor light fitting, excellent for lighting your property and with its grill detailing it is protected from any low level knocks. Ideal for use along walkways, pavements or either side of a doorway and with its opal coloured diffuser this fitting is perfect installed at any height without risk of glare. Versatile in nature this fitting is ideal for use on with the wall or ceiling with impact-resistant synthetic covers made of polycarbonate. Available in a choice of three fabulous colour finishes, white, Black, or silver grey.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	94-v0 Fire-rated PC diffuser
Beam Angle	90°
Color Available	White, Black & Dark-Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~2240V

Working Temperature	-10C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL348012	12W	LED	1440lm	275 X 70 mm
LP-ODL348024	24W	LED	2880lm	275 X 70 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.