

TENDER TEXT



WALL SURFACE

Star II

LP-ODL343624



TENDER TEXT

Supply and install Star II (LP-ODL343624) Wall Surface by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: 94-v0 Fire-rated PC Diffuser. Beam Angle: 90° / 120°. Color Available: White, Black & Dark-Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Star-II LED Fixture for illuminating common or outdoor areas near homes, is suitable for indoor and outdoor areas, with ceiling or wall installation where more intense and diffused lighting is required. It is particularly suited for lighting stairs, building entrance areas, corridors in shopping malls, shops, hotels & restaurants. Possibility of customizing it by changing the type of light source. The wide range of Light Plus sources with LED and CFL sources or even to transform it into emergency lighting.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	94-v0 Fire-rated PC Diffuser
Beam Angle	90° / 120°
Color Available	White, Black & Dark-Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-10C° ~ 50C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL343624	24W	LED	2880lm	187 X 93 X 300 mm
LP-ODL343636	36W	LED	4320lm	187 X 93 X 300 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.